

IN THE CLAIMS

1. (currently amended) A method for mounting a motor to a support, said method comprising:

providing a mounting system, the mounting system including a plurality of fasteners, the motor including a pair of endshields and a housing extending therebetween, the housing including a plurality of recessed openings, an outer surface, an inner surface, a housing body extending between the inner surface and the outer surface, and a plurality of raised projections, wherein each of the projections has a thickness that is equal to a thickness of the housing body;

attaching the fasteners through the openings formed in the housing, such that the fasteners extend radially outwardly through the housing and a head of the fasteners is substantially co-planar with an un-recessed portion of the inner surface of the housing and such that the head of the fasteners remain positioned between rotating components of the motor and the housing outer surface, wherein attaching the fasteners further comprises inserting each of the fasteners through a respective one of the plurality of raised projections such that the fasteners extend radially outwardly from the housing; and

attaching the motor to the support using the plurality of fasteners.

2. (previously presented) A method in accordance with Claim 1 wherein the plurality of raised projections are circumferentially spaced 90 degrees about the housing, each of the plurality of openings disposed within a respective raised projection, attaching the fasteners further comprising inserting each respective fastener through the respective housing raised projection.

3. (canceled)

4. (previously presented) A method in accordance with Claim 1 wherein attaching the fasteners further comprises crimping the fasteners to the inner surface of the housing.

5. (currently amended) A motor housing configured to receive a motor extending between a pair of endshields, said housing comprising:

an inner surface;

an outer surface, said inner surface configured to extend between a rotating component of the motor and said outer surface;

a housing body extending between said inner surface and said outer surface, said body comprising a thickness;

at least one raised projection extending radially outwardly from at least one of said housing inner surface and said housing outer surface defining a recess with respect to said housing inner surface of the housing body including an assembly of the rotating component and a stator of the motor, said projection comprising at least one opening extending therethrough, said at least one raised projection comprising an inner surface and a thickness equal to said housing body thickness; and

at least one fastener having a top surface, said at least one fastener extends outwardly through said housing opening such that said top surface is substantially coplanar with an un-recessed portion of said housing inner surface.

6. (original) A housing in accordance with Claim 5 wherein said housing further comprises a plurality of raised projections, said projections spaced circumferentially.

7. (original) A housing in accordance with Claim 5 wherein said housing further comprises a plurality of raised projections, adjacent said projections spaced circumferentially 90 degrees about the housing.

8. (original) A housing in accordance with Claim 5 wherein said housing comprises a cylindrical body.

9. (previously presented) A housing in accordance with Claim 5 wherein said inner surface of said at least one raised projection comprises at least one attachment point.

10. (previously presented) A housing in accordance with Claim 5 wherein said inner surface of said at least one raised projection comprises a plurality of attachment points configured to receive a fastener.

11. (previously presented) A housing in accordance with Claim 5 wherein said housing comprises a plurality of fasteners configured to attach to said inner surface of said at least one raised projection such that said fasteners extend outwardly from said housing.

12. (previously presented) A housing in accordance with Claim 5 wherein said at least one fastener is attached to said housing inner surface by at least one of a weld, a crimp, and an adhesive.

13. (previously presented) A housing in accordance with Claim 5 wherein said at least one fastener is attached to said inner surface of said raised projection such that said fasteners are disposed inside said housing inner surface.

14. (currently amended) A motor comprising:

a pair of endshields;

a housing extending between said endshields and including an assembly of a stator and a rotor, wherein said housing includes at least one raised projection extending outwardly from said housing, said housing comprising an outer surface, an opposite inner surface, and a body extending therebetween, said body comprising a thickness, said at least one raised projection defining a recess with respect to said housing inner surface and comprising an inner surface and a thickness equal to said housing body thickness, at least one opening extending through said recess, and at least one fastener having a top surface, said at least one fastener extends radially outwardly through said housing such that said top surface is substantially co-planar with said inner surface; ~~and~~

~~a stator-rotor assembly mounted in said housing, such that, wherein~~ said housing inner surface extends between said stator-rotor assembly and said housing outer surface.

15. (original) A motor in accordance with Claim 14 wherein said housing further comprises a plurality of raised projections, said projections spaced circumferentially 90 degrees about the housing.

16. (original) A motor in accordance with Claim 14 wherein said housing is substantially cylindrically shaped.

17. (previously presented) A motor in accordance with Claim 14 wherein said at least one raised projection comprises a plurality of attachment points configured to receive a fastener.

18. (previously presented) A motor in accordance with Claim 14 further comprising a plurality of fasteners configured to contact said inner surface of said at least one raised projection and extend outwardly from said housing through said opening.

19. (previously presented) A motor in accordance with Claim 18 wherein said plurality of fasteners are attached to said inner surface of said at least one raised projection by at least one of a weld, a crimp, and an adhesive.

20. (previously presented) A motor in accordance with Claim 14 wherein said at least one fastener contacts said inner surface of said at least one raised projection such that a head of said at least one fastener is substantially co-planar with said housing inner surface.